



75010012



IP21

KNX data interface USB RMD KNX, light grey

Technical features

Architecture

Fixing mode	REG
-------------	-----

Compatibility

Compatibility	compatible with USB 1.1/2.0 transmission protocols
System requirements:	system requirements: Windows 2000 or later

Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no
- with B-type USB socket for data traffic (voltage supply via PC)	

Voltage

Operating voltage over bus	21...32 V DC
----------------------------	--------------

Storage

Data transmission rate	max. 9,6 kBd
------------------------	--------------

Materials

Colour of design line	light grey
Colour independent of design lines	light grey
Colour	light grey
RAL colour	RAL 7035 - Light grey
Material	Plastic/metal
Surface appearance	other

Dimensions

Depth	70 mm
Assembling height as from DIN rail	63 mm
Width of rail mounted device (RMD)	2 modules
Height	90 mm
Width	36 mm

Cable

USB cable length	max. 5 m
------------------	----------

Settings

Supported configuration modes	system
- programmable from ETS3, V1.0	

Equipment

Interface type	USB
----------------	-----

Software

Update	with flash-controller technology
--------	----------------------------------

Safety

Protection index IP	IP21
Halogen free	no

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - system units
Main design line	KNX