



6768803515



Socket outlet insert with earthing pin and hinged cover surface-mounted/flush-mounted with enhanced touch protection, Berker W.1, grey matt

Technical features

Architecture

Fixing mode	flush-mounting or surface-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour of design line	grey
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

- with plug-in terminals

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
<hr/>	
<ul style="list-style-type: none">- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.	
<hr/>	