



50453515

Push-button insert, NO contact with rocker surface-mounted/flush-mounted Berker W.1

Technical features

Architecture

Type of control unit	rocker
----------------------	--------

Main electrical features

Nominal voltage	250 V
-----------------	-------

Rated voltage	250 V AC
---------------	----------

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

Colour of design line	grey
-----------------------	------

Colour	iron grey
--------	-----------

Colour	dark grey
--------	-----------

RAL colour	RAL 7011 - Iron grey
------------	----------------------

Material	Plastic/metal
----------	---------------

Surface appearance	mat
--------------------	-----

Dimensions

Depth	42 mm
-------	-------

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

- with plug-in terminals

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature	-40...30 °C
-----------------------	-------------

Storage/transport temperature	-50...50 °C
-------------------------------	-------------

Identification

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.