



30653515



**Blind series switch insert 1pole with rocker 2gang with imprinted symbol Arrows surface-mounted/flush-mounted Berker W.1, grey matt**

Technical features

#### Architecture

Type of control unit	double rocker
Fixing mode	flush-mounting

#### Configuration

- with mechanical and electrical interlock to prevent mutual switch-on

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Switching current	10 AX
-------------------	-------

#### Materials

Colour of design line	grey
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Depth	42 mm
Height	71 mm
Width	71 mm

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

- with plug-in terminals

#### Cable

- with cable entry at top and bottom

#### Safety

Protection index IP	IP55
---------------------	------

#### Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.

---