



50763505

**IP55**

**Push-button change-over contact, illuminated surface-mounted with lens, Berker W.1, grey/light grey matt**

Technical features

**Configuration**

- ample room for wiring under the bases of the inserts

**Main electrical features**

Rated voltage 250 V AC

**Electric current**

Momentary-contact current 10 A

**Materials**

Colour of design line grey/light grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

**Dimensions**

Depth 61,5 mm

Height 76 mm

Width 76 mm

**Connection**

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals
- with N-terminal

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with 230 V LED unit
- for lighting and monitoring circuit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Use**

Differentiation characteristic 2 - Sales with lens

**Safety**

Protection index IP IP55

**Use conditions**

Operating temperature -40...30 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---