



50453525



IP55

## Push-button, NO contact surface-mounted Berker W.1

### Technical features

#### Architecture

Type of control unit single rocker

#### Configuration

- ample room for wiring under the bases of the inserts

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

#### Electric current

Momentary-contact current 10 A

#### Materials

Colour of design line grey

Colour light grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material Plastic/metal

Surface appearance matt

#### Installation, mounting

Installation mode for screw fastening

#### Connection

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

#### Safety

Protection index IP IP55

#### Use conditions

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

#### Identification

Main design line Berker W.1

**Instructions**

---

Information text

Pins of quick-release lock made of ZAMAK

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-