



50763555

IP55

Push-button, change-over contact surface-mounted with labelling field - illuminated, Berker W.1, grey/light grey matt

Technical features

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Rated voltage 250 V AC

Electric current

Momentary-contact current 10 A

Materials

Colour of design line grey/light grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

Dimensions

Labelling field (W x H) 50 x 16 mm

Height 76 mm

Width 62 mm

Connection

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with N-terminal
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with 230 V LED unit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 1 - Sales with labelling field - illuminated

Safety

Protection index IP IP55

Use conditions

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK, For labelling with name, information notice, etc., Labelling field height arranged for P-touch strips 12 mm.
------------------	--
