



50753515



**IP55**

**Series push-button, 2 change-over contacts surface-mounted, isolated input terminals Berker W.1, grey/light grey matt**

#### Technical features

#### Configuration

- ample room for wiring under the bases of the inserts

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |

#### Electric current

|                           |      |
|---------------------------|------|
| Momentary-contact current | 10 A |
|---------------------------|------|

#### Materials

|                       |                      |
|-----------------------|----------------------|
| Colour of design line | grey/light grey      |
| Colour                | iron grey            |
| Colour                | dark grey            |
| RAL colour            | RAL 7011 - Iron grey |
| Material              | thermoplastic        |
| Surface appearance    | matt                 |

#### Dimensions

|        |       |
|--------|-------|
| Depth  | 76 mm |
| Height | 76 mm |
| Width  | 62 mm |

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | for screw fastening |
|-------------------|---------------------|

#### Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

#### Safety

|                     |      |
|---------------------|------|
| Protection index IP | IP55 |
|---------------------|------|

#### Use conditions

|                               |             |
|-------------------------------|-------------|
| Operating temperature         | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

**Identification**

|                    |                                       |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line   | Berker W.1                            |

**Instructions**

|                  |  |
|------------------|--|
| Information text | Pins of quick-release lock made of ZAMAK |
|------------------|--|