



6765792089



**Socket outlet with earthing pin Installation position variable in 45° steps, with enhanced touch protection, with screw-in lift terminals, Serie R.classic, polar white glossy**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

#### Dimensions

Insertion depth	31,4 mm
-----------------	---------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

#### Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

#### Equipment

Type of configuration	Laserdruck
-----------------------	------------

#### Use

Differentiation characteristic 1 - Sales	Installation position variable in 45° steps
Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

---

**Safety**

---

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

---

**Identification**

---

Main design line	Serie R.classic
------------------	-----------------

---