glossy

Painted



75163590

IP20

B.IQ push-button 3gang comfort KNX - Berker B.IQ, glass polar white

Technical features

Architecture

Fiving mode	fluch recording
Fixing mode	flush-mounting
Technical version	3gan
Functions	
With room temperature controller	n
- for switch, push-button, dimmer and shutter functions	
Compatibility	
 extension unit for light scene push-button 	
Controls and indicators	
With LED indication	уе
Number of buttons	
 activation of second user level via object one push-button operation for switching, pushing, shutters and dimmir 	ng
Measurement	
 value transmitter for dimming, position, brightness and temperature va 	lues 1 and 2 byte
Screen	
With display	n
Materials	
Colour of design line	glass polar whit
Colour	polarwhit
RAL colour	RAL 9010 - Pure whit
Material	glas

Material Surface appearance

Dimensions

Type of surface treatment

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 6 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



Settings

Supported configuration modes	system, PE
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
 for installation in single standard wall boxes for additional products to complement the installation in matchi platform S.1/B.x for glass frames in the same "style" for additional applications, s 	
Equipment	
Number of actuation points	
With anti-theft/dismantling protection	yes
Product type:	product type: B.IC
Safety	
Protection index IP	IP20
Halogen free	n
 with dismantling protection alarm telegram after disconnection from bus coupling unit 1 bit 	or 1 byte
Use conditions	
	-545 °C
Operating temperature	
Identification	KNX - operating systems
Identification Application, usage	
	KNX - operating systems product family: push-buttor KNX - Berker B.IC