

75162000	
75163099	

**IP20** 

## B.IQ push-button 3gang KNX - Berker B.IQ, polar white matt

Technical features

	cture

Fixing mode	flush-mounting
Technical version	3gang

### **Functions**

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

# Compatibility

- extension unit for light scene push-button

### **Controls and indicators**

With LED indication	yes
Number of buttons	3

### Measurement

- dimming / position value transmitter 1 byte

### Screen

With display	no
--------------	----

### Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt
Type of surface treatment	untreated
Material family	Plastic

#### **Dimensions**

Height	88,5 mm
Width	88,5 mm

## **LED** control

LED	with blue operation LED and 6 white status LEDs
	(labelling field illumination)

## Connection

- for bus coupling unit flush-mounted

### Scope of delivery

Bus connection included	no



# **Accessories included**

Inscribable, with labelling field	no
<ul> <li>for installation in single standard wall boxes</li> <li>for additional products to complement the installation in matching colours/materials, refer to the De platform S.1/B.x</li> <li>for plastic frames in the same "style" for additional applications, see the Design line B.7</li> </ul>	
Equipment	
Number of actuation points	6
With anti-theft/dismantling protection	yes
Type of configuration	Laserdruck
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
- with dismantling protection	
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX