



75168694



B.IQ push-button 4gang for light scenes KNX - Berker B.IQ, Aluminium, aluminium anodised

Technical features

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

With room temperature controller	no
----------------------------------	----

- light scene push-buttons can be cascaded
- retrieval, adjustment and storage of 8 light scenes

Controls and indicators

With LED indication	yes
---------------------	-----

Number of buttons	4
-------------------	---

- second operating level for setting load groups via 3-button actuation

Measurement

- dimming / position value transmitter 1 byte

Screen

With display	no
--------------	----

Materials

Colour of design line	Aluminium
-----------------------	-----------

Colour	aluminium
--------	-----------

RAL colour	RAL 9006 - White aluminium
------------	----------------------------

Material / workmanship	aluminium, anodised
------------------------	---------------------

Material	Aluminium
----------	-----------

Surface appearance	matt
--------------------	------

Type of surface treatment	Anodised
---------------------------	----------

Dimensions

Assembling height	16,7 mm
-------------------	---------

Height	118,1 mm
--------	----------

Width	88,5 mm
-------	---------

LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	---

Connection

Number of load groups (increase on cascading)	8
---	---

- for bus coupling unit flush-mounted

Scope of delivery

Bus connection included	no
-------------------------	----

Accessories included

Inscribable, with labelling field	no
- for installation in single standard wall boxes	
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x	
- for aluminium frames in the same "style" for additional applications, see the Design line B.7	

Equipment

Number of actuation points	8
With anti-theft/dismantling protection	yes
Light scenes	max. 8
Product type:	product type: B.IQ

Safety

Protection index IP	IP20
Halogen free	no
- with dismantling protection	

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ