



41350007



SCHUKO socket outlet with enhanced touch protection, Screw-in lift terminals, Berker Arsys Kupfer Med, copper, natural metal

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	Copper
Colour	copper
Colour	copper optics
RAL colour	RAL 8004 - Copper brown
Material / workmanship	metal natural
Material	Copper
Surface appearance	mat

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to VDE 0620-1:2021-02
- with screw-in lift terminals	

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

Safety

IK protection code against mechanical impacts	07
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker Arsys Kupfer Med
------------------	-------------------------