product sheet 20300002





20300002



Functions	
- with on/off switch and indicator LED for "on"	
Main electrical features	
Nominal voltage	250 \
Rated voltage	250 V A0
Frequency	50/60 H
Electric current	
Inductive load at $\cos \varphi$ = 0.6	max. 4 /
Switching current "Heating" at $\cos \varphi = 0.6$	4,
Heating switching current	10 /
Switching current	10 /
Measurement	
Range of temperatures	5 / 30 °C
Materials	
Colour of design line	whit
Colour	whit
Material	Plastic/meta
Dimensions	
Insertion depth	24,5 mn
Installation, mounting	
Installation mode	without spreader claws
Connection	
Connection	with separate connection for night lowering
- with plug-in terminals	
Equipment	
Night lowering	≈ 4
Switching temperature difference	≈ 0,5
 setting knob with temperature range limitation e.g. for valve drives closed in de-energised state 	
Use	
Differentiation characteristic 1 - Sales	with rocker switc
Use conditions	
Energy efficiency class	l (1%
- with thermal return	

Temperature controller, NC contact, with centre plate with rocker switch, Berker Arsys, white glossy



temperatur	
Temperature	530 °C
Identification	
Application, usage	HVAC control
Main design line	Berker Arsys