product sheet 3315410069



3315410069

Architecture	
Technical version	with screw-in lift termina
Connectivity	
 with straight outlet S-VGA compatible with 15pole D-subminiature jack (front) 	
Frequency	
Frequency range video	max. 160 Mł
Screen	
Resolution	max. 1280 x 1024
Materials	
Colour of design line	polar wh
Colour	polarwh
RAL colour	RAL 9010 - Pure wh
Material	Plastic/met
Surface appearance	glos
Installation, mounting	
Installation mode	without spreader claws, for screw fastening
Connection	
Conductor cross-section	max. 1,5 mr
 with screw-in lift terminals for connection to 15-c 	ore VGA cable
Equipment	
- with supporting ring	
Use	
Differentiation characteristic 3 - Sales	with screw-in lift termina
Identification	
Application, usage	Communication technolo
Main design line	Berker Ars



Instructions

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74