



85141131



IP20

## Button 1gang Berker R.1/R.3/R.8/Serie 1930/R.classic, black glossy

### Technical features

### Controls and indicators

- with 2-push-buttons operation concept

### Main electrical features

Nominal voltage 12 V

### Voltage

Operating voltage via insert

### Measurement

Relative humidity (without condensation) 0...65 % (without condensation)

### Materials

Colour of labelling 217,217,217

Colour of design line black

Colour black

Material thermoplastic

Material for printing PC-PMA black

### Dimensions

Diameter 57,4 mm

### Settings

Shading parameter R1\_czarny

Laser parameter R1\_schwarz

### Equipment

Type of configuration Laserdruck

- switch-on brightness level for use on dimmer insert, power failure proof, storable

### Use conditions

Operating temperature -5...45 °C

- low intrinsic energy requirement

### Identification

Application, usage Light control

Main design line Berker R.1/R.3/R.8/Serie 1930/R.classic

Secondary design line(s) Electronics platform, Berker R.1, Berker R.3, Berker R.8

### Instructions

- Note:

When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!