



47393505



**IP55**

**SCHUKO socket outlet with hinged cover surface-mounted with labelling field, Lock - differing lockings, enhanced contact protection, Berker W.1, grey/light grey matt**

Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

#### Configuration

- ample room for wiring under the bases of the inserts

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

#### Materials

Colour of design line	grey/light grey
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Insertion depth	32 mm
Labelling field (W x H)	50 x 16 mm
Height	76 mm
Width	76 mm

#### Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

#### Connection

Conductor cross-section	1...2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

### Cable

- with one entry for 2 cables and one entry for cable and tube

### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

### Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	Lock - differing lockings
Differentiation characteristic 3 - Sales	enhanced contact protection

### Safety

Protection index IP	IP55
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
- with 2 keys	

### Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

### Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

### Instructions

Information text	Labelling field height arranged for P-touch strips 12 mm., Spare keys and other closures (max. 24) on request., Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--