



47703525



IP55

**SCHUKO socket outlet 2gang vertical with hinged cover surface-mounted Berker W.1, grey/light grey matt**

Technical features

**Architecture**

Design according to DIN 49440

Fixing mode surface-mounting

**Configuration**

- ample room for wiring under the bases of the inserts

**Connectivity**

Type of USB port other

**Main electrical features**

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

**Electric current**

Rated current 16 A

**Cover, door**

Cover Complete housing

- with hinged cover that falls back, manual clip-in

**Materials**

Colour of design line grey/light grey

Colour iron grey

Colour dark grey

RAL colour RAL 7011 - Iron grey

Material thermoplastic

Surface appearance matt

**Installation, mounting**

Installation mode for vertical mounting, for screw fastening

**Connection**

Conductor cross-section 1...2,5 mm<sup>2</sup>

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

**Cable**

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

---

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

---

**Safety**

IK protection code against mechanical impacts 05

Protection index IP IP55

---

- without enhanced contact protection

---

**Use conditions**

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

---

**Identification**

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

---

**Instructions**

Information text Hinged cover springs made of stainless steel, pins  
of quick-release lock made of ZAMAK

---