



47703535



IP55

**SCHUKO socket outlet 2gang vertical with hinged cover surface-mounted with labelling field, Berker W.1, grey/light grey matt**

#### Technical features

#### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | surface-mounting       |

#### Configuration

- ample room for wiring under the bases of the inserts

#### Connectivity

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Cover, door

|       |   |
|-------|---|
| Cover | Complete housing                                  |
| -     | with hinged cover that falls back, manual clip-in |

#### Materials

|                       |                      |
|-----------------------|----------------------|
| Colour of design line | grey/light grey      |
| Colour                | iron grey            |
| Colour                | dark grey            |
| RAL colour            | RAL 7011 - Iron grey |
| Material              | thermoplastic        |
| Surface appearance    | matt                 |

#### Dimensions

|                         |            |
|-------------------------|------------|
| Labelling field (W x H) | 50 x 16 mm |
| Height                  | 147 mm     |
| Width                   | 76 mm      |

#### Installation, mounting

|                   |  |
|-------------------|--|
| Installation mode | for vertical mounting, for screw fastening |
|-------------------|--|

### Connection

|  |                                 |
|--|---------------------------------|
| Conductor cross-section  | 1...2,5 mm <sup>2</sup>         |
| Connection terminals   | according to IEC 60884-1        |
| Connection terminals   | according to VDE 0620-1:2021-02 |
| <ul style="list-style-type: none"><li>- with two clip-in places for Wago 2-wire connection terminals in the housing floor</li><li>- with Wago clip-in 2-wire connection terminal for wiring</li><li>- with plug-in terminals</li></ul> |                                 |

### Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

### Use

|  |                      |
|--|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
|--|----------------------|

### Safety

|   |      |
|---|------|
| IK protection code against mechanical impacts   | 05   |
| Protection index IP   | IP55 |
| <ul style="list-style-type: none"><li>- without enhanced contact protection</li></ul> |      |

### Use conditions

|                               |             |
|-------------------------------|-------------|
| Operating temperature         | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

### Identification

|                    |                                       |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line   | Berker W.1                            |

### Instructions

|                  |  |
|------------------|--|
| Information text | Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK |
|------------------|--|