



SCHUKO socket outlet 2gang horizontal with hinged cover surface-mounted with labelling field, enhanced contact protection, Berker W.1, polar white matt

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour of design line	polar white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Dimensions

Labelling field (W x H)	50 x 16 mm
Height	76 mm
Width	147 mm

Connection

Conductor cross-section	1...2,5 mm ²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

47753552



IP55

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 1 - Sales with labelling field
Differentiation characteristic 2 - Sales enhanced contact protection

Safety

IK protection code against mechanical impacts 05
Protection index IP IP55
Enhanced contact protection according to IEC 60884-1
Enhanced contact protection according to VDE 0620-1:2021-02
- Enhanced contact protection

Use conditions

Operating temperature -40...30 °C
Storage/transport temperature -50...50 °C

Identification

Application, usage Surface-mounted wet-room installation
Main design line Berker W.1

Instructions

Information text Hinged cover springs made of stainless steel, pins
of quick-release lock made of ZAMAK