



47843535



IP55

SCHUKO socket outlet 2gang horizontal with hinged cover surface-mounted with enhanced touch protection, Berker W.1

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting
Technical version	2 cable entries

Configuration

- ample room for wiring under the bases of the inserts

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour of design line	grey/light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	mat

Connection

Conductor cross-section	1...2,5 mm ²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

Safety

IK protection code against mechanical impacts	05
---	----

Protection index IP	IP55
---------------------	------

Enhanced contact protection	according to IEC 60884-1
-----------------------------	--------------------------

Enhanced contact protection	according to VDE 0620-1:2021-02
-----------------------------	---------------------------------

- Enhanced contact protection	
-------------------------------	--

Use conditions

Operating temperature	-40...30 °C
-----------------------	-------------

Storage/transport temperature	-50...50 °C
-------------------------------	-------------

Identification

Application, usage	Surface-mounted wet-room installation
--------------------	---------------------------------------

Main design line	Berker W.1
------------------	------------

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--
