



**SCHUKO socket outlet 3gang horizontal with hinged cover surface-mounted Berker W.1, polar white matt**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	surface-mounting

**Configuration**

- ample room for wiring under the bases of the inserts

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
-------	------------------

- with hinged cover that falls back, manual clip-in

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for horizontal mounting, for screw fastening
-------------------	--

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

**Cable**

- inserts wired-through
- with one entry for 2 cables and 2 entries for cable and tube

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

47733512



IP55

---

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP55
- without enhanced contact protection	

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--

---