




3146



IP66

**Control rotary switch off/change-over surface-mounted with red lens, Isopanzer IP66, dark grey/yellow**

Technical features

**Architecture**

Type of control unit	Short thumb-grip
Fixing mode	surface-mounting

**Configuration**

- Off/change-over

**Controls and indicators**

- No

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Switching current	16 AX
-------------------	-------

**Materials**

Colour of design line	dark grey/yellow
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Depth	56 mm
Height	75 mm
Width	75 mm

**Fluorescent bulbs control**

Neon lamp current	2,7 mA
-------------------	--------

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Type of connection	Screw connection
<ul style="list-style-type: none"> <li>- with additional terminal, e.g. for control switch function</li> <li>- with screw terminals</li> </ul>	

**Cable**

- with cable entry at top and bottom

**Equipment**

- for lighting and monitoring circuit

**Use**

---

Differentiation characteristic 2 - Sales with red lens

---

**Safety**

---

Protection index IP IP66

---

**Identification**

---

Application, usage Surface-mounted wet-room installation

---

Main design line Isopanzer IP66

---

**Instructions**

---

Information text Housing screws made of stainless steel.

---