



4286



IP44

Socket outlet with earthing contact and hinged cover USA/CANADA NEMA 5-15 R surface-mounted Screw terminals, Isopanzer IP44, dark grey/yellow

Technical features

Architecture

Fixing mode	surface-mounting
- 2pole + earth	

Configuration

- ample room for wiring under the bases of the inserts
--

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50 Hz
Rated current	15 A

Cover, door

Cover	Complete housing
-------	------------------

Materials

Colour of design line	dark grey/yellow
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Conductor cross-section (rigid)	max. 2 x 4 mm ²
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	Screw terminals
--	-----------------

Standards

Standard	NEMA 5-15 R
----------	-------------

Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Isopanzer IP44

Instructions

Information text

Housing screws, hinged cover springs and axles
made of stainless steel.
