



181113



Push-button, NO contact Berker TS, stainless steel matt, brushed nickel

Technical features

Architecture

Type of control unit	Push button
----------------------	-------------

Configuration

- Normally open contact

Main electrical features

Nominal voltage	12 V
-----------------	------

Rated voltage	12 V
---------------	------

Electric current

Momentary-contact current	1,5 A
---------------------------	-------

Materials

Colour of design line	stainless steel
-----------------------	-----------------

Colour	stainless steel
--------	-----------------

Colour	stainless steel optics
--------	------------------------

RAL colour	RAL 9022 - Pearl light grey
------------	-----------------------------

Material / workmanship	Nickel brushed
------------------------	----------------

Material	nickel
----------	--------

Surface appearance	matt
--------------------	------

- brass, refined

Dimensions

Depth	19,7 mm
-------	---------

Insertion depth	13 mm
-----------------	-------

Height	22 mm
--------	-------

Width	22 mm
-------	-------

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

- with plug-in terminals

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-20...60 °C
-----------------------	-------------

Identification

Main design line	Berker TS
------------------	-----------

Instructions

- For connection via system interfaces to radio bus, KNX radio or KNX installations.

Alternatively, can be used to control relay circuits.
