



75664599



B.IQ push-button 4gang with thermostat Display, KNX - Berker B.IQ, polar white matt

Technical features

Architecture

Technical version 4gang

Functions

With room temperature controller yes

Operating mode controller operating modes: comfort, standby, night and frost/heat protection mode

- for switch, push-button, dimmer, blind and thermostat functions
- with valve protection function
- button help function can be activated
- with room temperature timer and 2-week timer functions

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication yes

Dimming area dimming

Number of buttons 4

- text display (ASCII-format)
- one push-button operation for switching, pushing, shutters and dimming
- blind operating concepts short-long-short and long-short parameterisable
- display of operating mode, controller lockout, room/outside temperature, time (clock required)
- LC display with symbols and illumination, switchable via object
- with 2 additional display buttons

Connectivity

- with button blocking function

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display yes

Materials

Colour of labelling 105,105,105

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

Material family Plastic

Dimensions

Assembling height 15 mm

Height 149,2 mm

Width 88,5 mm

LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	---

Connection

- For flush-mounted bus coupling unit for B.IQ with thermostat

Settings

- single and two push-button operation parameterisable
- end customer display scope parameterisable
- presence button parameterisable to extend comfort
- programmable from ETS2, V1.2a

Accessories included

Inscribable, with labelling field	no
-----------------------------------	----

- for installation in single standard wall boxes
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
- for plastic frames in the same "style" for additional applications, see the Design line B.7

Equipment

Number of actuation points	10
----------------------------	----

Type of configuration	Laserdruck
-----------------------	------------

Product type:	product type: B.IQ
---------------	--------------------

- for heating and/or cooling mode with/without auxiliary step
- control parameter for heating / cooling unit pre-set
- for individual single room temperature control
- for continuous (PI) or switched (2-point) control of max. 2 control circuits

Use

Differentiation characteristic 2 - Sales	Display
--	---------

Software

Update	with flash-controller technology
--------	----------------------------------

Safety

Halogen free	no
--------------	----

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit, 1 or 2 byte

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Energy efficiency class	IV (2%)
-------------------------	---------

- provision of the internal temperature value via communication object
- temperature measurement via internal temperature sensor and/or external communication object (weighting ratio parameterisable)

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Release issue	2.6
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ
