



41699011



Socket outlet with earthing contact USA/CANADA NEMA 5-20 R with screw terminals, Berker Arsys, light bronze matt, lacquered

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	20 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	light bronze
Colour	bronze
Colour	hellbronze optics
RAL colour	RAL 3012 - Beige red
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	matt

Dimensions

Insertion depth	19 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---------------------------------------------

Connection

Conductor cross-section (rigid)	max. 2 x 4 mm ²
Connection terminals	according to IEC 60884-1
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	with screw terminals
------------------------------------------	----------------------

Standards

Standard	NEMA 5-20 R
----------	-------------

Safety

IK protection code against mechanical impacts	02
Enhanced contact protection	according to IEC 60884-1
- without enhanced contact protection	

Identification

Main design line	Berker Arsys
------------------	--------------

Instructions

Information text	Not UL-certified.
------------------	-------------------
