



Socket outlet with earthing contact SWITZERLAND type 12, 3gang, can be switched off with enhanced touch protection, Plug-in terminals, Berker K.5

Technical features

Architecture

| | |
|-----------------|----------------|
| Fixing mode | flush-mounting |
| - 2pole + earth | |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Rated current | 10 A |

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------|---------------|
| Colour of design line | Aluminium |
| Material / workmanship | metal |
| Material | thermoplastic |

Connection

| |
|--------------------------|
| - with plug-in terminals |
|--------------------------|

Use

| | |
|--|--------------------------------|
| Differentiation characteristic 2 - Sales | with enhanced touch protection |
| Differentiation characteristic 3 - Sales | Plug-in terminals |

Safety

| | |
|-------------------------------|---------------------------------|
| Enhanced contact protection | according to IEC 60884-1 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection | |

Identification

| | |
|--------------------------|------------|
| Main design line | Berker K.5 |
| Secondary design line(s) | Berker K.5 |