

75161593

IP20

B.IQ push-button 1gang comfort KNX - Berker B.IQ, Stainless steel, metal brushed

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	1gang
Functions	
With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	
Compatibility	
- extension unit for light scene push-button	
Controls and indicators	yes
- extension unit for light scene push-button Controls and indicators With LED indication Number of buttons	у

- one push-button operation for switching, pushing, shutters and dimming

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display	no

Materials

Colour of design line	Stainless steel
Colour	stainless steel
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal brushed
Material	stainless steel
Surface appearance	matt
Type of surface treatment	brushed

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 2 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



Settings

Supported configuration modes	system, PE
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
 for installation in single standard wall boxes for additional products to complement the installation in match platform S.1/B.x for stainless steel frames in the same "style" for additional apple 	
Equipment	
Number of actuation points	:
With anti-theft/dismantling protection	yes
Product type:	product type: B.IC
Safety	
Protection index IP	IP20
Halogen free	na
 with dismantling protection alarm telegram after disconnection from bus coupling unit 1 bit 	t or 1 byte
Use conditions	
	-545 °C
Operating temperature	
Operating temperature Identification	
	KNX - operating systems
Identification	KNX - operating systems product family: push-buttor
Identification Application, usage	