



47753522



IP55

**SCHUKO socket outlet 2gang horizontal with hinged cover surface-mounted Berker W.1, polar white matt**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	surface-mounting
Technical version	4 cable entries

**Configuration**

- ample room for wiring under the bases of the inserts

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
-------	------------------

- with hinged cover that falls back, manual clip-in

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for horizontal mounting, for screw fastening
-------------------	--

**Connection**

Conductor cross-section	1...2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

---

**Cable**

---

- inserts wired-through
  - 2 additional side cable entries
  - with one entry for 2 cables and one entry for cable and tube
- 

**Equipment**

---

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- 

**Safety**

---

- |   |      |
|---|------|
| IK protection code against mechanical impacts | 05   |
| Protection index IP                           | IP55 |
- without enhanced contact protection
- 

**Use conditions**

---

- |                               |             |
|-------------------------------|-------------|
| Operating temperature         | -40...30 °C |
| Storage/transport temperature | -50...50 °C |
- 

**Identification**

---

- |                    |                                       |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line   | Berker W.1                            |
- 

**Instructions**

---

- |                  |   |
|------------------|---|
| Information text | As a result of the side cable entries specially suited for installation over workbenches., Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK |
|------------------|---|
-