



SCHUKO socket outlet 3gang horizontal with hinged cover surface-mounted Berker W.1, grey/light grey matt

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour of design line	grey/light grey
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

Installation, mounting

Installation mode	for horizontal mounting, for screw fastening
-------------------	--

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with two clip-in places for Wago 2-wire connection terminals in the housing floor	
- with Wago clip-in 2-wire connection terminal for wiring	
- with plug-in terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and 2 entries for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

47733515



IP55

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP55
- without enhanced contact protection	

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--
