



47087003



SCHUKO socket outlet with residual current circuit-breaker enhanced contact protection, Berker K.5, aluminium, matt, lacquered

**Technical features** 

hitecture	

Design	according to DIN 49440
Fixing mode	flush-mounting
- type A for alternating currents and pulsating direct currents	

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

# **Electric current**

Measurement error current	30 mA
Rated current	16 A
Surge current resistance	250 A (8/20) µs
Short-circuit resistance (with back-up fuse 20 AqL)	3 kA

# Tripping

Trigger time	≤ 30 ms
--------------	---------

### Cover, door

Cover Central cover p	plate
-----------------------	-------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	Plastic/metal
Surface appearance	matt

# **Dimensions**

Insertion depth	31,9 mm
-----------------	---------

# Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

## Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	



Use	
Differentiation characteristic 2 - Sales	enhanced contact protection
Standards	
Tested	conform VDE 0664 (EN 61008)
Safety	
IK protection code against mecanical impacts	07
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker K.5