



6768740007



Socket outlet with earthing pin with enhanced touch protection, Berker Arsys Kupfer Med, copper, natural metal

**Technical features** 

| Arc | hite | ctur | e |
|-----|------|------|---|
|     |      |      |   |

| Fixing mode     | flush-mounting |
|-----------------|----------------|
| - 2pole + earth |                |

#### Main electrical features

| Nominal voltage | 250 V    |
|-----------------|----------|
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

# Cover, door

| Cover Central cover | r plate |
|---------------------|---------|
|---------------------|---------|

#### Materials

| Colour of design line  | Copper                  |
|------------------------|-------------------------|
| Colour                 | copper                  |
| Colour                 | copper optics           |
| RAL colour             | RAL 8004 - Copper brown |
| Material / workmanship | metal natural           |
| Material               | Copper                  |
| Surface appearance     | matt                    |

# **Dimensions**

| Insertion depth | 31,2 mm |
|-----------------|---------|
|-----------------|---------|

## Installation, mounting

| with spreader claws |
|---------------------|
|                     |

# Connection

| Connection terminals     | according to IEC 60884-1 |
|--------------------------|--------------------------|
| - with nlug-in terminals |                          |

### Use

| Differentiation characteristic 2 - Sales | with enhanced touch protection |
|--|--------------------------------|
|--|--------------------------------|

# Safety

| IK protection code against mecanical impacts | 07                       |
|--|--------------------------|
| Enhanced contact protection                  | according to IEC 60884-1 |
| - Enhanced contact protection                |                          |

# Identification

| Main design line | Berker Arsys Kupfer Med |
|------------------|-------------------------|
|------------------|-------------------------|