



47582004



SCHUKO socket outlet with hinged cover with labelling field, Berker Arsys IP44, stainless steel, metal matt finish

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	Stainless steel
Colour	stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal, matt finish
Material	stainless steel
Surface appearance	matt

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

Safety

IK protection code against mechanical impacts	07
Protection index IP	IP20
- without enhanced contact protection	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Arsys IP44

Instructions

Information text	Labelling field height arranged for P-touch strips 6 mm.
------------------	--

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 101000).
-