flush-mounting



75860073

**IP20** 

### Info display Stainless steel, metal matt finish

**Technical features** 

Fixing mode

## **Controls and indicators**

- for max. 48 signalling groups
- to display and initiate actions -
- LC display with illumination

# Materials

| Colour of design line     | Stainless steel             |
|---------------------------|-----------------------------|
| Colour                    | stainless steel             |
| RAL colour                | RAL 9022 - Pearl light grey |
| Material / workmanship    | metal, matt finish          |
| Material                  | thermoplastic               |
| Surface appearance        | matt                        |
| Type of surface treatment | Painted                     |
|                           |                             |

### Connection

- for bus coupling unit flush-mounted

## Settings

0

| Supported configuration modes     | system                     |
|-----------------------------------|----------------------------|
| - programmable to 1, 2 or 4 lines |                            |
| Equipment                         |                            |
| Product type:                     | product type: LCD displays |
| - with piezo signal generator     |                            |
| Safety                            |                            |
| Halogen free                      | no                         |

- with dismantling protection - visual/acoustic alarm message, acknowledgable

#### Use conditions

| Dperating temperature | -545 °C |
|-----------------------|---------|
|-----------------------|---------|

## Identification

| Application, usage       | KNX - operating systems |
|--------------------------|-------------------------|
| Product family           | product family: display |
| Secondary design line(s) | KNX, Berker K.5         |