



47403515



IP55

SCHUKO socket outlet with hinged cover surface-mount. Berker W.1, grey/light grey matt

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with Wago clip-in 2-wire connection terminal for wiring	
- with two clip-in places for Wago 2-wire connection terminals in the housing floor	
- with plug-in terminals	

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
- without enhanced contact protection	

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	---
