



47633502



IP55

SCHUKO socket outlet with hinged cover surface-mounted with enhanced touch protection, Berker W.1, polar white matt

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with two clip-in places for Wago 2-wire connection terminals in the housing floor	
- with Wago clip-in 2-wire connection terminal for wiring	
- with plug-in terminals	

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 2 - Sales with enhanced touch protection

Safety

IK protection code against mechanical impacts 05

Protection index IP IP55

Enhanced contact protection according to IEC 60884-1

Enhanced contact protection according to VDE 0620-1:2021-02

- Enhanced contact protection

Use conditions

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

Identification

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

Instructions

Information text Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK