



50763502



IP55

Push-button change-over contact, illuminated surface-mounted with lens, Berker W.1, polar white matt

Technical features

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Momentary-contact current	10 A
---------------------------	------

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	61,5 mm
Height	76 mm
Width	76 mm

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals
- with N-terminal

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with blue 230 V LED unit
- for lighting and monitoring circuit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 2 - Sales	with lens
--	-----------

Safety

Protection index IP	IP55
---------------------	------

Use conditions

Operating temperature -40...30 °C

Identification

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

Instructions

Information text Pins of quick-release lock made of ZAMAK
