



50763552



IP55

**Push-button, change-over contact surface-mounted with labelling field - illuminated, Berker W.1, polar white matt**

Technical features

**Configuration**

- ample room for wiring under the bases of the inserts

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Momentary-contact current	10 A
---------------------------	------

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Labelling field (W x H)	50 x 16 mm
Height	76 mm
Width	62 mm

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with N-terminal
- with plug-in terminals

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- with (blue) 230 V LED unit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Use**

Differentiation characteristic 1 - Sales	with labelling field - illuminated
--	------------------------------------

**Safety**

Protection index IP	IP55
---------------------	------

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Labelling field height arranged for P-touch strips 12 mm., Labelling fields with imprinted symbol for light, bell and door opener enclosed, Pins of quick-release lock made of ZAMAK, For labelling with name, information notice, etc.
------------------	---

---