




35623502



IP55

**Control on/off switch 2pole with imprint "Heizung - 0 - I" surface-mounted with lens, Berker W.1, polar white matt**

Technical features

### Architecture

Fixing mode surface-mounting

### Connectivity

- with mechanical encoding of rocker mount, that allows only one correct positioning of the rocker on the insert

### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

### Electric current

Switching current 10 A

### Materials

Colour of design line polar white

Colour white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

### Dimensions

Depth 62 mm

Height 76 mm

Width 76 mm

### Installation, mounting

Installation mode for screw fastening

### Connection

Type of connection Quickconnect

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

### Cable

- with one entry for 2 cables and one entry for cable and tube

### Equipment

- with 230 V LED unit
- for monitoring circuit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- Not suitable for heating systems > 50 kW.

---

**Use**

---

Differentiation characteristic 2 - Sales with lens

---

**Safety**

---

Protection index IP IP55

---

**Use conditions**

---

Operating temperature -40...30 °C

---

Storage/transport temperature -50...50 °C

---

**Identification**

---

Application, usage Surface-mounted wet-room installation

---

Main design line Berker W.1

---

**Instructions**

---

Information text Pins of quick-release lock made of ZAMAK

---