



75162099

IP20

B.IQ push-button 2gang KNX - Berker B.IQ, polar white matt

Technical features

Architecture

| | |
|-------------------|----------------|
| Fixing mode | flush-mounting |
| Technical version | 2gang |

Functions

| | |
|---|----|
| With room temperature controller | no |
| - for switch, push-button, dimmer and shutter functions | |

Compatibility

- extension unit for light scene push-button

Controls and indicators

| | |
|---------------------|-----|
| With LED indication | yes |
| Number of buttons | 2 |

Measurement

- dimming / position value transmitter 1 byte

Screen

| | |
|--------------|----|
| With display | no |
|--------------|----|

Materials

| | |
|---------------------------|-----------------------|
| Colour of labelling | 105,105,105 |
| Colour of design line | polar white |
| Colour | polarwhite |
| RAL colour | RAL 9010 - Pure white |
| Material | thermoplastic |
| Surface appearance | matt |
| Type of surface treatment | untreated |
| Material family | Plastic |

Dimensions

| | |
|--------|----------|
| Depth | 16,65 mm |
| Height | 88,5 mm |
| Width | 88,5 mm |

LED control

| | |
|-----|--|
| LED | with blue operation LED and 4 white status LEDs (labelling field illumination) |
|-----|--|

Connection

- for bus coupling unit flush-mounted

Scope of delivery

| | |
|-------------------------|----|
| Bus connection included | no |
|-------------------------|----|

Accessories included

| | |
|--|----|
| Inscribable, with labelling field | no |
| - for installation in single standard wall boxes | |
| - for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x | |
| - for plastic frames in the same "style" for additional applications, see the Design line B.7 | |

Equipment

| | |
|--|--------------------|
| Number of actuation points | 4 |
| With anti-theft/dismantling protection | yes |
| Type of configuration | Laserdruck |
| Product type: | product type: B.IQ |

Safety

| | |
|-------------------------------|------|
| Protection index IP | IP20 |
| Halogen free | no |
| - with dismantling protection | |

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

Identification

| | |
|--------------------------|-----------------------------|
| Application, usage | KNX - operating systems |
| Product family | product family: push-button |
| Main design line | KNX - Berker B.IQ |
| Secondary design line(s) | KNX, Berker B.IQ |
