



75164094

IP20

**B.IQ push-button 4gang KNX - Berker B.IQ, Aluminium, aluminium anodised**

Technical features

**Architecture**

|                   |                |
|-------------------|----------------|
| Fixing mode       | flush-mounting |
| Technical version | 4gang          |

**Functions**

|   |    |
|---|----|
| With room temperature controller                        | no |
| - for switch, push-button, dimmer and shutter functions |    |

**Compatibility**

- extension unit for light scene push-button

**Controls and indicators**

|                     |     |
|---------------------|-----|
| With LED indication | yes |
| Number of buttons   | 4   |

**Measurement**

- dimming / position value transmitter 1 byte

**Screen**

|              |    |
|--------------|----|
| With display | no |
|--------------|----|

**Materials**

|                           |                            |
|---------------------------|----------------------------|
| Colour of design line     | Aluminium                  |
| Colour                    | aluminium                  |
| RAL colour                | RAL 9006 - White aluminium |
| Material / workmanship    | aluminium, anodised        |
| Material                  | Aluminium                  |
| Surface appearance        | matt                       |
| Type of surface treatment | Anodised                   |
| Material family           | Metal                      |

**Dimensions**

|                   |          |
|-------------------|----------|
| Assembling height | 16,7 mm  |
| Height            | 118,1 mm |
| Width             | 88,5 mm  |

**LED control**

|     |   |
|-----|---|
| LED | with blue operation LED and 8 white status LEDs |
|-----|---|

**Connection**

- for bus coupling unit flush-mounted

**Scope of delivery**

|                         |    |
|-------------------------|----|
| Bus connection included | no |
|-------------------------|----|

---

**Accessories included**

---

|   |    |
|---|----|
| Inscribable, with labelling field   | no |
| <ul style="list-style-type: none"><li>- for installation in single standard wall boxes</li><li>- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x</li><li>- for aluminium frames in the same "style" for additional applications, see the Design line B.7</li></ul> |    |

---

**Equipment**

---

|  |                    |
|--|--------------------|
| Number of actuation points             | 8                  |
| With anti-theft/dismantling protection | yes                |
| Product type:                          | product type: B.IQ |

---

**Safety**

---

|   |      |
|---|------|
| Protection index IP   | IP20 |
| Halogen free  | no   |
| <ul style="list-style-type: none"><li>- with dismantling protection</li></ul> |      |

---

**Use conditions**

---

|                       |            |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

---

**Identification**

---

|                          |                             |
|--------------------------|-----------------------------|
| Application, usage       | KNX - operating systems     |
| Product family           | product family: push-button |
| Main design line         | KNX - Berker B.IQ           |
| Secondary design line(s) | KNX, Berker B.IQ            |

---