



20262089



Thermostat, change-over contact, with centre plate Berker R.1/R.3/R.8, polar white glossy

Technical features

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |

Electric current

| | |
|--|------|
| Switching current "Heating" at $\cos \varphi = 0.6$ | 4 A |
| Heating switching current | 10 A |
| "Switching current ""Cooling"" at $\cos \varphi = 0.6$ " | 2 A |
| "Switching current ""Cooling""" | 5 A |

Measurement

| | |
|-----------------------|-----------|
| Range of temperatures | 5 / 30 °C |
|-----------------------|-----------|

Materials

| | |
|-----------------------|---------------|
| Colour of design line | polar white |
| Colour | polarwhite |
| Material | Plastic/metal |

Installation, mounting

| | |
|-------------------|------------------------|
| Installation mode | without spreader claws |
|-------------------|------------------------|

Connection

- with screw terminals

Equipment

| | |
|---|---------|
| Switching temperature difference | ≈ 0,5 K |
| <ul style="list-style-type: none"> - for heating or cooling mode - setting knob with temperature range limitation - e.g. for valve drives closed in de-energised state | |

Use conditions

| | |
|---|--------|
| Energy efficiency class | I (1%) |
| <ul style="list-style-type: none"> - with thermal return | |

temperatur

| | |
|-------------|-----------|
| Temperature | 5...30 °C |
|-------------|-----------|

Identification

| | |
|--------------------------|------------------------------------|
| Application, usage | HVAC control |
| Main design line | Berker R.1/R.3/R.8 |
| Secondary design line(s) | Berker R.1, Berker R.3, Berker R.8 |

Instructions

- Note:

When integrating this product into the Serie 1930, the 1 gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!
