



75261671



IP20

KNX controller comfort 2.2 m KNX - Berker K.5, aluminium matt, lacquered

Technical features

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

Max. temporisation	306 h
Potentiometer for additional delay time	± 50 %
<ul style="list-style-type: none"> - Functions for lighting operating mode: Switching, Value transmitter and Light scene call - parameter definable lock function - with slide switch for OFF/automatic/ON 	

Compatibility

- also suitable as extension unit

Controls and indicators

Number of switching segments	72
------------------------------	----

Power

Power consumption, KNX	≈ 110 mW
------------------------	----------

Measurement

Detection field, semi-oval shaped	≈ 12 x 12 m
-----------------------------------	-------------

Reach distance

Range, frontal	≈ 12 m
Range, frontal (at 1.1 m installation height)	≈ 6 m
Range, side	each ≈ 6 m
Range, side (at 1.1 m installation height)	each ≈ 3 m
Max. transmission range frontally	12 m
Max. transmission range sideways	6 m

Cover, door

Cover	with cover to limit detection angle to 90°
-------	--

Detection

Number of detection levels	2
Detection angle	180 °
Detection angle vertical	0 / 7 °
Detection angle horizontal	0 / 180 °
Sensor type	detector of movement

Materials

Colour of design line	aluminium
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

Dimensions

Dimensions assembling height	23,5 mm
Nominal mounting height	2,2 m
Optimum mounting height	2,2 m

Lighting control

Response brightness, configurable	3...100 lx / daytime operation
-----------------------------------	--------------------------------

LED control

LED	with red diagnostic LED for brightness-independent walk test function and disassembly message
-----	---

Connection

- for bus coupling unit flush-mounted

Settings

Supported configuration modes	system
Response brightness adjustable by potentiometer	± 50 %
Response sensitivity, settable	20...100 %
Min. temporisation	130 ms
Delay time	≈ 10 s
Additional delay time programmable	130 ms...306 h
- with potentiometers for fine adjustment of the response brightness, sensitivity and delay time	

Equipment

Product type:	product type: movement
- with lighting and message mode	

Safety

Protection index IP	IP20
Halogen free	no
- alarm telegram after disconnection from bus coupling unit, 1-bit	

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - sensors
Product family	product family: physical sensors
Main design line	KNX - Berker K.5
Secondary design line(s)	Motion detector, KNX, Berker K.5

Instructions

Information text

Application as for order no. 7526 15 ..

Caution:
Direct sunlight can lead to false alarms when using
alarm application. Avoid using detection field
equipment on windows.
