



47290069 ____

Double SCHUKO socket outlet with frame enhanced contact protection, Berker Arsys, polar white glossy

Technical features

	nite	

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	itral cover pl	late
-------	----------------	------

Materials

polar white
polarwhite
white
RAL 9010 - Pure white
duroplastic
glossy

Dimensions

Insertion depth	32 mm
Assembling height	22 mm

Installation, mounting

For installation in 1gang wall boxes	according to DIN 49073-1	
Installation mode	with spreader claws	

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------



Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker Arsys