




41436084



**SCHUKO socket outlet with screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9**

Technical features

**Architecture**

Design according to DIN 49440

Fixing mode flush-mounting

**Connectivity**

Type of USB port other

**Main electrical features**

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

**Electric current**

Rated current 16 A

**Cover, door**

Cover Central cover plate

**Materials**

Colour of design line aluminium

Colour aluminium

Colour aluminium optics

RAL colour RAL 9006 - White aluminium

Material / workmanship lacquered

Material thermoplastic

Surface appearance velvety

**Dimensions**

Insertion depth 32 mm

Installation depth, flush-mounted boxes 31 mm

**Installation, mounting**

Installation mode with spreader claws

**Connection**

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with screw-in lift terminals

**Use**

Differentiation characteristic 3 - Sales with screw-in lift terminals

---

**Safety**

---

|   |      |
|---|------|
| IK protection code against mechanical impacts | 02   |
| Protection index IP                           | IP20 |
| - without enhanced contact protection         |      |

---

**Identification**

---

|                          |  |
|--------------------------|--|
| Main design line         | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

---