



3036



## Change-over switch Light control

### Technical features

### Architecture

Type of control unit	single rocker
Fixing mode	flush-mounting

### Functions

Switching angle	3,5 °
-----------------	-------

### Configuration

- Off/change-over

### Controls and indicators

- No

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

### Electric current

Switching current	10 AX (100 W Self Ballasted Lamp (SBL))
-------------------	---

### Materials

Material	Plastic/metal
Surface appearance	mat

### Dimensions

Depth	42 mm
Insertion depth	31 mm
Height	71 mm
Width	71 mm

### Installation, mounting

Installation mode	with spreader claws, for screw fastening
-------------------	--

### Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	Quickconnect
- with plug-in terminals	

### Equipment

- for lighting and monitoring circuit

---

**Safety**

---

Protection index IP	IP20
Impact strength	IK07

---

**Identification**

---

Application, usage	HVAC control, Light control
Appliance switch type	No
Main design line	Light control

---

**Instructions**

---

Information text	spreader claws, insulated to the supporting ring, self-resetting
------------------	--

---

- A control change-over switch is shown here as an example. With 2-pole and 3-pole control on/off switches, other rocker switches and neon lamp units are required.
-