



28850001



Ceiling loudspeaker Ø 140 mm Communication technology, white

Technical features

Frequency

Frequency response (-3 dB)	170...22000 Hz
----------------------------	----------------

Power

Nominal/music power handling	6/8 W
------------------------------	-------

Resistance

Impedance	8 Ω
-----------	-----

Detection

- at 1 kHz	180 °
- at 4 kHz	130 °
- at 8 kHz	80 °

Materials

Colour independent of design lines	white
Material	Mixed materials

Dimensions

Insertion depth	62 mm
Installation opening Ø	116 mm
Recommended installation height	2,4...4 m
Installation wall thickness	30 mm
Loudspeaker chassis Ø	87 mm

Installation, mounting

Installation mode	with spring mechanism for ceiling installation
-------------------	--

Connection

Conductor cross-section (flexible)	max. 2,5 mm ²
- with plug-in terminals	

Cable

- with strain relief	
----------------------	--

Equipment

Sound pressure level 1 W/1 m	87 dB
Sound pressure level at rated power	95 dB

Safety

- with membrane impregnated against humidity	
--	--

Identification

Application, usage	Communication technology
Main design line	Communication technology

Instructions

Information text	Suitable installation housings available from Kaiser and Spelsberg.
------------------	--
