



41086089



**SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety**

Technical features

**Architecture**

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

**Controls and indicators**

- with acoustic fault signal

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

**Voltage**

|                        |   |
|------------------------|---|
| Overvoltage protection | according to EN 61643 and VDE 0675-6-11 |
|------------------------|---|

**Electric current**

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

**Cover, door**

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

**Materials**

|                       |                       |
|-----------------------|-----------------------|
| Colour of design line | polar white           |
| Colour                | polarwhite            |
| Colour                | white                 |
| RAL colour            | RAL 9010 - Pure white |
| Material              | thermoplastic         |
| Surface appearance    | velvety               |

**Dimensions**

|                 |       |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

**Installation, mounting**

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

**Connection**

|                        |                                 |
|------------------------|---------------------------------|
| Connection terminals   | according to IEC 60884-1        |
| Connection terminals   | according to VDE 0620-1:2021-02 |
| - with screw terminals |                                 |

**Equipment**

- with indicator LED for On/Error

---

**Use**

---

|  |                      |
|--|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
| Differentiation characteristic 3 - Sales | Screw terminals      |

---

**Safety**

---

|   |      |
|---|------|
| IK protection code against mechanical impacts | 05   |
| Protection index IP                           | IP20 |
| - without enhanced contact protection         |      |

---

**Identification**

---

|                          |  |
|--------------------------|--|
| Main design line         | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

---

**Instructions**

---

|                  |  |
|------------------|--|
| Information text | Labelling field height arranged for P-touch strips 6 mm. |
|------------------|--|

---