



4211



IP44

**SCHUKO socket outlet with cover plate and hinged cover Screw terminals, Splash-protected flush-mounted IP44, grey glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Full cover plate
-------	------------------

**Materials**

Colour independent of design lines	Grey
Colour	light grey
Colour	grey
RAL colour	RAL 7035 - Light grey
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Insertion depth	32 mm
-----------------	-------

**Installation, mounting**

Installation mode	without spreader claws, for single mounting, for screw fastening
-------------------	--

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

**Accessories included**

- with flush-mounted box

**Equipment**

- with sealing cup

**Use**

Differentiation characteristic 3 - Sales	Screw terminals
--	-----------------

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	

---

**Identification**

---

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

---